



Preem Diesel

Product description

Preem Diesel consists of 100% diesel in accordance with NS-EN590.

Benefits

Stricter requirements for vehicle exhaust gases necessitate a well-functioning engine. Preem Diesel contains ACP, Preem's multifunction additive. This additive contains deposit control compounds that counteract the formation of deposits in the injection system and protects the fuel system against rust. A clean engine gives optimal combustion, which contributes to reducing environmentally harmful emissions. The ACP additive is expected to give lower fuel consumption compared to diesel without ACP and can contribute to extending engine life.

Preem Diesel contains a lubricating additive that minimises wear on the fuel system.

Applications

Preem Diesel is suitable not only for light and heavy engines, but also for old and new engines.

Storage

All diesel must be stored in containers that are approved for storage. To ensure that the product quality is not degraded, containers permeable to light must not be used. When diesel fuel is stored, it is important to check for water in the containers regularly to reduce the risk of microorganism growth.

Health, safety and environment

See the Safety Data Sheet.

Specifications

NS-EN590

Article codes

09614 (summer)

09606 (winter)

09625 (spring/autumn)

17700

Summer:	1. April to 15. September.
Spring/fall:	1. March to 31. march, and 16. September to 31. October
Winter:	1. November to 28. February.

Unless otherwise agreed, the temperature properties when leaving the main terminal will comply with this table +/- 14 days.



Preem Diesel

Properties	Unit	Requirements (NS-EN590)
Cetane number	-	min 51,0
Density at 15°C	kg/m ³	820,0 – 845,0 800,0 – 840,0*
Sulphur content (mass content)	mg/kg	max 10,0
Flash point	°C	>55,0
Viscosity at 40°C	mm ² /s (cSt)	2,00 – 4,50 1,50 – 4,00*
<i>Distillation:</i> Temp for 95% distillate	°C	max 360 max 340*
<i>Cold filter plugging point (CFPP)</i> summer spring/fall winter	°C	max -11 max -24 max -32
<i>Cloud point (Cloud Point)</i> summer spring/fall winter	°C	max 0 max -15 max -22

*Limits for winter quality diesel