



Gasoline 95 E5

Bensin 95 E5

Product description

Gasoline 95 E5 is a high-quality petrol containing bioethanol and a multifunction additive.

Benefits

5% bioethanol has been added to Gasoline 95 E5 to reduce the emission of fossil CO₂.

The product contains an additive that cleans and maintains the engine fuel system.

The additive also provides good corrosion protection for the fuel system.

Applications

Gasoline 95 E5 can be used in all gasoline engines that can run on 95 octane gasoline.

Storage

All gasoline must be stored in containers that are approved for storage. To ensure that the product quality is not degraded, containers permeable to light must not be used.

Health, Safety and the Environment

See the Safety Data Sheet

Specifications

- NS-EN 228

Article code

- 13300



Gasoline 95 E5

Properties	Units	Requirements in accordance with NS-EN 228
Octane number	RON	min 95.0
Density at 15°C	kg/m ³	720 - 775
Flash point	°C	Below -40
Sulphur	mg/kg	max 10*
Benzene	volume %	max 1.0*
Vapour pressure at 37.8°C (RVP)		
summer	kPa	45 - 70*
other seasons of the year	kPa	70 - 100
Evaporated at 70°C (E70)		
summer	volume %	20 – 48
other seasons of the year	volume %	22 – 50
at 100°C (E100)	volume %	46* – 71
at 150°C (E150)	volume %	min 75*
Final Boiling Point	°C	max 210

*Regulated by the authorities