



Marine Gasoil 1000 ppm

Marine Gassolje 1000 ppm

Product description

Marine Gasoil 1000 ppm is a light distillate to which marker and dye have been added in accordance with the authorities requirements for low-tax products.

Benefits

The product has good functionality and reduces emission of SO_x.

Applications

Marine Gasoil 1000 ppm is used as a fuel in marine diesel engines for which use of low-tax fuels is permitted.

Storage

The product must only be stored in tanks approved for storage. To ensure that the product quality is not degraded, tanks that are permeable to light must not be used. During storage, it is important to check the water in the containers regularly to reduce the risk of microorganism growth.

Health, Safety and the Environment

See the Safety Data Sheet

Specifications

- Norsk Bransjestandard for Petroleumsprodukter, Marine Gassolje [Norwegian Industry Standard for Petroleum Products, Marine Gasoil]
- ISO 8217, DMA

Article code

- 21300



Marine Gasoil 1000 ppm

Properties	Units	Requirements
Density at 15°C	kg/m ³	max 860
Viscosity at 40°C	mm ² /s (cSt)	2.0 - 4.0
Sulphur content	weight %	max 0.1
Flash point	°C	min 60*
Cetane index		min 45
Distilled at 350°C	volume %	min 85
Cloud Point	°C	max 0
Cold Filter Plugging Point (CFPP)	°C	max -11
Carbon residue (Ramsbottom 10 vol%)	Mass %	max 0.2

* International requirement.